



Product Service

CERTIFICATE

No. Z1 124139 0004 Rev. 00

Holder of Certificate: **SPA Corp Europe S.L.**
Poligono Industrial El Pintero C/Tejedores 22
41410 Carmona (Sevilla)
SPAIN

Certification Mark:



Product: **Scaffold**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: MES1477441624A00TR

Valid until: 2028-04-12

Date, 2024-01-17

(Andrea Rotundo)

CERTIFICATE

No. Z1 124139 0004 Rev. 00

Model(s):

14H0442; 14H0443; 14H0444; 14H0445; 14H0446;
14H0447; 14H0448; 14H0449; 14H0450; 14H0451;
14H0452; 14H0453; 14H0454; 14H0455; 14H0456;
14H0457; 14H0458; 14H0459; 14H0460; 14H0461;
14H0462; 14H0463; 14H0464; 14H0465; 14H0466;
14H0467; 14H0468; 14H0469; 14H0470; 14H0471;
14H0472; 14H0473; 14H0474; 14H0475; 14H0476;
14H0477; 14H0478; 14H0479; 14H0480; 14H0481;
14H0482; 14H0483; 14H0484; 14H0485; 14H0518;
14H0519; 14H0520; 14H0521; 14H0522; 14H0523;
14H0524.

Parameters:

Scaffold				
Code Model	Max dimensions [m] [LxWxH]	Max standing height [m]	Dead Load	Castor Type Ø [mm]
14H0442	2,55x1,35x3,73 5,18x3,98x3,73 *	2,3	158	200
14H0443	2,55x1,35x4,64 5,18x3,98x4,64 *	3,2	165	200
14H0444	2,55x1,35x5,84 5,18x3,98x5,84 *	4,4	213	200
14H0445	2,55x1,35x6,74 5,18x3,98x6,74 *	5,3	220	200
14H0446	2,55x1,35x7,94 5,18x3,98x7,94 *	6,5	268	200
14H0447	2,55x1,35x8,85 5,18x3,98x8,85 *	7,4	275	200
14H0448	2,55x1,35x10,05 5,18x3,98x10,05 *	8,6	324	200
14H0449	2,55x1,35x10,96 5,18x3,98x10,96 *	9,5	331	200
14H0450	2,55x1,35x12,16 5,18x3,98x12,16 *	10,7	379	200
14H0451	2,55x1,35x13,06 5,18x3,98x13,06 *	11,6	386	200
14H0452	1,96x1,35x3,73 4,59x3,98x3,73 *	2,3	141	200
14H0453	1,96x1,35x4,64 4,59x3,98x4,64 *	3,2	148	200
14H0454	1,96x1,35x5,84 4,59x3,98x5,84 *	4,4	189	200
14H0455	1,96x1,35x6,74 4,59x3,98x6,74 *	5,3	196	200
14H0456	1,96x1,35x7,94 4,59x3,98x7,94 *	6,5	238	200
14H0457	1,96x1,35x8,85 4,59x3,98x8,85 *	7,4	245	200
14H0458	1,96x1,35x10,05 4,59x3,98x10,05 *	8,6	286	200
14H0459	1,96x1,35x10,96 4,59x3,98x10,96 *	9,5	293	200
14H0460	1,96x1,35x12,16 4,59x3,98x12,16 *	10,7	334	200
14H0461	1,96x1,35x13,06 4,59x3,98x13,06 *	11,6	342	200

CERTIFICATE

No. Z1 124139 0004 Rev. 00

Scaffold				
Code Model	Max dimensions [m] [LxWxH]	Max standing height [m]	Dead Load	Castor Type Ø [mm]
14H0462	2,55x0,73x3,73 5,18x3,36x3,73 *	2,3	127	200
14H0463	2,55x0,73x4,64 5,18x3,36x4,64 *	3,2	132	200
14H0464	2,55x0,73x5,84 5,18x3,36x5,84 *	4,4	176	200
14H0465	2,55x0,73x6,74 5,18x3,36x6,74 *	5,3	182	200
14H0466	2,55x0,73x7,94 5,18x3,36x7,94 *	6,5	226	200
14H0467	2,55x0,73x8,85 5,18x3,36x8,85 *	7,4	231	200
14H0468	2,55x0,73x10,05 5,18x3,36x10,05 *	8,6	276	200
14H0469	2,55x0,73x10,96 5,18x3,36x10,96 *	9,5	281	200
14H0470	2,55x0,73x12,16 5,18x3,36x12,16 *	10,7	326	200
14H0471	2,55x0,73x13,06 5,18x3,36x13,06 *	11,6	331	200
14H0472	1,96x0,73x3,73 4,59x3,36x3,73 *	2,3	116	200
14H0473	1,96x0,73x4,64 4,59x3,36x4,64 *	3,2	122	200
14H0474	1,96x0,73x5,84 4,59x3,36x5,84 *	4,4	159	200
14H0475	1,96x0,73x6,74 4,59x3,36x6,74 *	5,3	164	200
14H0476	1,96x0,73x7,94 4,59x3,36x7,94 *	6,5	202	200
14H0477	1,96x0,73x8,85 4,59x3,36x8,85 *	7,4	207	200
14H0478	1,96x0,73x10,05 4,59x3,36x10,05 *	8,6	245	200
14H0479	1,96x0,73x10,96 4,59x3,36x10,96 *	9,5	250	200
14H0480	1,96x0,73x12,16 4,59x3,36x12,16 *	10,7	288	200
14H0481	1,96x0,73x13,06 4,59x3,36x13,06 *	11,6	293	200
14H0482	1,96x0,73x1,96 2,48x1,25x1,96 *	0,9	54	125
14H0483	2,48x1,25x3,28 2,48x1,25x3,28 *	1,8	75	125
14H0484	1,96x0,73x5,39 4,44x3,21x5,39 *	3,9	131	125
14H0485	1,96x0,73x7,5 4,44x3,21x7,5 *	6	178	125
14H0522	1,61x0,78x3,73 3,99x3,36x3,73 *	2,3	98	125
14H0523	1,61x0,78x5,84 3,99x3,36x5,84 *	4,4	134	125
14H0524	1,61x0,78x7,94 3,99x3,36x7,94 *	6,5	171	125
14H0518	1,32x0,73x2,68 2,32x1,92x2,68 *	1,2	62	125
14H0519	1,32x0,73x3,88 2,84x2,43x3,88 *	2,4	73	125

CERTIFICATE

No. Z1 124139 0004 Rev. 00

Scaffold				
Code Model	Max dimensions [m] [LxWxH]	Max standing height [m]	Dead Load	Castor Type Ø [mm]
14H0520	1,32x0,73x5,08 2,84x2,43x5,08*	3,6	96	125
14H0521	1,32x0,73x6,28 2,84x2,43x6,28*	4,8	107	125

Material:

Parameters: Group according to EN 1004-1:2020 = 3

Max.loading capacity = 2,0 kN/m²

Note: * with stabilizers

Frame: EN AW6063 T5

Rung: EN AW6063 T5

Platform frame: EN AW6063 T5

Platform: EN 636 Class Plywood (thickness=12 mm.)

Toeboard: EN 636 Class Plywood (thickness=12 mm.)

Tested according to: PPP 52015D:2022
EN 1004-1:2020
EN 1004-2:2021