

LUBRIFICADOR
ENGRASADOR
GRAISSEUR
SCHMIERNIPPEL
LUBRICATION POINT

CREMALHEIRA E CARRETO EM FERRO FUNDIDO
CORONA Y PIÑON EN HIERRO FUNDIDO
COURONNE ET PIGNON EN FONTE
ZAHNKRAANZ UND ZAHNRAD AUS GUSSEISEN
CAST IRON GEAR RING

BOCA REFORÇADA
BALDE COM 3 AMASSADORES DUPLOS SOLDADOS
BOCA REFORZADA, BOMBO
CON 3 PALAS MEZCLADORAS DOBLES SOLDADOS
OUVERTURE RENFORCÉE
3 PALES DOUBLES DE MALAXAGE MÉCANO-SOUDÉE
VERSTÄRKTÉ ÖFFNUNG
TROMMEL MIT 3 GESCHWEIßTE DOPPEL-MISCHSCHAUFELN
DRUM WITH REINFORCED OPENING
3 DOUBLE MIXING BLADES

PROTEÇÃO DE CREMALHEIRA OPCIONAL
PROTECCIÓN DE RACK OPCIONAL
PROTECTION DE LA COURONE EN OPTION
ZAHNRADSCHUTZ ALS OPTION
OPTIONAL GEAR RING PROTECTION



OPÇÃO OPCIÓN OPTION OPTION OPTION



CONTA HORAS
CONTA HORAS
COMPTÉUR D'HEURES
STUNDENZÄHLER
HOUR METER



ARRANQUE ELÉCTRICO
ARRANQUE ELÉCTRICO
DÉMARRAGE ÉLECTRIQUE
ELEKTRO STARTER
ELECTRIC STARTER

BP N

BETONEIRA PROFISSIONAL
HORMIGONERA PROFESIONAL
BÉTONNIÈRE PROFESSIONNELLE
PROFI BETONMISCHER
PROFESSIONAL CEMENT MIXER



Cremalheira e carreto em ferro fundido
Corona y piñon en hierro fundido
Couronne et pignon en fonte
Zahnkranz aus Gußeisen
Cast iron gear ring

Suporte de fixação
Soporte de montaje
Pieds stabilisateurs
Haltewinkel
Support

Pedal reforçado
Pedal reforzado
Pédale renforcée
Robuster pedal
Reinforced pedal

500 N

400 N

330 N

280 N

DOSAGEM CAPACIDAD
DOSAGE DOSIERUNG
DOSAGE

SEM MOTOR SIN MOTOR
SANS MOTEUR OHNE MOTOR
WITHOUT ENGINE

PRODUÇÃO HORÁRIA PRODUCCIÓN
HORARIA PRODUCTION HORAIRE
STUNDENPRODUKTION
PRODUCTION PER HOUR

TOTAL BALDE MÁX. DEL BOMBO
CAPACITÉ DE LA CUVE
TROMMELINHALT DRUM CAPACITY

MÁX. DE MISTURA MÁX. DE MEZCLA
MAX DE MALAXAGE
MISCHLEISTUNG MAX. MIXING

DIMENSÕES DIMENSIONS
DIMENSIONS DIMENSIONEN
DIMENSIONS



2 x 50 Kg + 25 Kg

35 Kg + 35Kg

35 Kg + 25Kg

25 Kg + 25Kg



210 Kg

171 Kg

149 Kg

126 Kg



3,30 m3/h

2,60 m3/h

2,40 m3/h

2,00 m3/h



450 L

360 L

320 L

260 L



390 L

290 L

255 L

200 L



1810 x 1100 x 1650 mm

1810 x 1100 x 1650 mm

1810 x 1100 x 1650 mm

1665 x 910 x 1465 mm



SIRL 3,0 hp
500 N



SIRL 2,0 hp
400 N 330 N 280 N

ELÉTRICO ELECTRICO ÉLECTRIQUE ELEKTRO ELECTRIC



KM173F 3,8 hp

KOHLER 15LD 225 4,5 hp

KOHLER KD15-350 7,0 hp

DIESEL



HONDA GX 160 5,5 hp

BRIGGS & STRATTON CR 950 6,5hp



EX 17 5,7 hp

GASOLINA GASOLINA ESSENCE BENZIN PETROL