

CD UNIVERSAL PLATE CLAMP

CD型竖吊钢板起重吊钳

WORKING LOAD LIMIT(WLL)500-30000KGS

- For lifting and transporting steel plates and structures from all positions (horizontal, vertical and sidelong).
- Articulated lifting shackle.
- CD lifting clamps are equipped with a pre-tension mechanism ensuring the clamp does not slip when lifting force is applied and when load is being lowered.
- The clamp is locked in closed as well as in open position.
- Minimum W.L.L. is 10 % of the maximum W.L.L.

NB: The plate surface of the material must have a hardness level below HRC30/Brinell 300





INSPECTION, CARE & USE

DO NOT lift loads less than 10% of working load limit of clamp
DO NOT lift plates with a temperature greater than 100°C
DO NOT use to lift stainless steel, lead or copper.

For more information, visit us at
www.mertex.net



**LIFTING LONG
PLATES WITH A
2 LEGGED
CHAIN SLING**



Code	Model	Jaw Opening [mm]	Load Capacity [kg]	T [mm]	U [mm]	V [mm]	L [mm]	Net Weight [kg]
90301	CD0.5T	0-15	500	205	30	105	48	2
90303	CD1T	0-20	1000	300	50	145	66	5
90305	CD2T	0-25	2000	385	68	175	75	8
90307	CD3.2T	0-30	3200	430	75	215	102	15
90309	CD5T	0-50	5000	500	68	232	112	23
90310	CD8T	0-45	8000	600	88	290	125	37
90311	CD12T	50-90	12000	700	90	420	128	50
90312	CD16T	60-100	16000	710	100	445	128	65
90313	CD20T	0-80	20000	948	100	563	140	160
90314	CD30T	10-90	30000	944	100	568	142	167